

LX Swimming pool pump SWIM025 SWIM035 SWIM050 SWIM075 SWIM100 SWIM150



Swimming pool pumps SWIM025 SWIM035 SWIM050 SWIM075 SWIM100 SWIM150

Description:

Suitable for the circulation and filtration of water in a Spa and also in medium and large-size Swimming Pools.

Also used in Water treatment plants and Ornamental Pools etc

Features:

1. Electric pump over-current components using high-strength engineering plastics with high-quality wear-resistant mechanical seal (SUS316), available for both fresh water and sea water.
2. With self-priming , maximum 2.5m
3. Motor with 71 frame
4. Pump uses a low noise standard motor. Single-phase with thermal protector KLIXON from TI,USA.
5. Motors have high temperature bearings, long operating life with reliability and durability
6. Complete separation of water and the axis, safe and reliable
7. Optional (ON/OFF) switch
8. Insulation class F, Protection IPX5.
9. The pump obtained the certification of TUV Rheinland
10. Replacement of ESPA SILEN

Working conditions

1. Medium temperature: 5-50 centigrade degree
2. Environmental temperature: below 60 centigrade degree
3. Max.working pressure: 0.3MPa

Technical Data

MODEL	POWER P1		Q max.	H Max.	Inlet/Outlet
	KW	Hp	L/min	M	mm
SWIM025	0.37	0.50	195	7	48.5/50
SWIM035	0.55	0.75	255	10	48.5/50
SWIM050	0.75	1.0	340	12.5	48.5/50
SWIM075	0.9	1.2	370	15	48.5/50
SWIM100	1.1	1.5	390	17.5	48.5/50
SWIM150	1.5	2.0	470	18.5	48.5/50